



ANTIQUÉ



DRIFTWOOD



NUTMEG



PECAN



SANDALWOOD



TOBACCO



WILLOW



WALNUT

<b>PRODUCT CODE(S):</b>	DF-PRI748-[COLOUR] Plank DF-PRIRED-[COLOUR] Reducer DF-PRITMLD-[COLOUR] T-Molding DF-PRISTR-[COLOUR] Stair Nose
<b>COLOURS:</b>	<b>ANTIQUÉ</b> [COLOUR CODE: ANT] <b>DRIFTWOOD</b> [COLOUR CODE: DFW] <b>NUTMEG</b> [COLOUR CODE: NMG] <b>PECAN</b> [COLOUR CODE: PEC] <b>SANDALWOOD</b> [COLOUR CODE: SWD] <b>TOBACCO</b> [COLOUR CODE: TOB] <b>WILLOW</b> [COLOUR CODE: WIL] <b>WALNUT</b> [COLOUR CODE: WLT]
<b>SIZE(S):</b>	7"x48" PLANK 95"x1.7"x0.4" REDUCER 95"x1.8"x0.3" T-MOLDING 95"x4.5"x1" STAIR NOSE
<b>MATERIAL:</b>	SPC CORE STRUCTURE W/CERAMIC BEAD FINISH & ATTACHED EVA ACOUSTIC PAD
<b>WEAR LAYER THICKNESS:</b>	20 MIL
<b>OVERALL THICKNESS:</b>	5.5 MM
<b>PLANKS/BOX:</b>	10/BOX
<b>COVERAGE/BOX:</b>	24.29 SF/BOX
<b>WEIGHT/BOX:</b>	38.3 LBS/BOX
<b>INSTALLATION:</b>	VÄLINGE 5Gi DROP LOCK FLOATING SYSTEM
<b>PRICE [PLANK]:</b>	\$117.81/BOX (\$4.85 SF) <i>*SOLD BY FULL BOX ONLY</i>
<b>PRICE [TRIMS]:</b>	REDUCER: \$15.00 EA T-MOLDING: \$15.00 EA STAIR NOSE: \$40.00 EA <i>*SOLD BY THE PIECE</i>
<b>WARRANTY:</b>	LIFETIME   RESIDENTIAL 17 YEAR   COMMERCIAL



T-MOLDING



REDUCER



STAIR NOSE



# VYLUXE LUXURY VINYL FLOORING BY EURO TILE

SERIES | PRIMOLUXE 5.5

## TECHNICAL DATA

Plank Size	7" x 48" x 5.5mm
Overall Thickness	5.5mm
Wear Layer Thickness	0.5mm
Planks Per Box	10 planks/box
Coverage [Square Feet Per Box]	24.29/box
Weight Per Box	38.3 lbs/box
Run Length	60 LF   Before requiring the use of a transition strip or molding
Temperature Restrictions	Can be installed in temperatures ranging from -20°C to + 80°C

Material	SPC Core Structure With Ceramic Bead Finish & Attached EVA Acoustic Pad
Installation	Välinge 5Gi Drop Lock Floating Installation System

## CONSTRUCTION & PERFORMANCE

Standard	ASTM F1700
Phthalate Safe	Yes
Printed Design	Hi-Definition Natural Stone Deep Embossing
Bevel Edge Profile	4 Sides

Impact Insulation Class	ASTM E492   IIC 73
Sound Transmission Class	ASTM E90   STC 61

Chemical & Stain Resistance	ASTM F925   Pass
Dimensional Stability	EN ISO 23999   Pass
Fire Rating	ASTM E648/662   Compliant
Resistance To Radiant Heat	Can be installed over hydronic radiant heated floors that use embedded cables <u>under</u> the subfloor. DO NOT INSTALL over any electric heating mat this is installed on-top of the subfloor. Do not turn heat above 29°C/85°F.
Slip Resistance	ASTM D2047   Compliant
Static Load Resistance	ASTM F970   Pass
Wheel Castor Resistance	ISO 4918   Pass

## SUSTAINABILITY & WARRANTY

Indoor Air Quality, VOC Emission	Phthalate Free   FloorScore Certified
Recyclable	100% Recyclable
Commercial Warranty	17 Years   Limited
Residential Warranty	Lifetime   Limited

EURO CERAMIC TILE DISTRIBUTORS LTD.

[www.eurotile.ca](http://www.eurotile.ca)

Shading and variation is inherent in luxury vinyl flooring. Please inspect before installing, no claims accepted after installation.